

MAINVIEW[®] for WebSphere MQ Integrator User Guide

Version 4.1

August 15, 2002



Copyright 2002 BMC Software, Inc., as an unpublished work. All rights reserved.

BMC Software, the BMC Software logos, and all other BMC Software product or service names are registered trademarks or trademarks of BMC Software, Inc. IBM and DB2 are registered trademarks of International Business Machines Corp. All other registered trademarks or trademarks belong to their respective companies.

THE USE AND CONTENTS OF THIS DOCUMENTATION ARE GOVERNED BY THE SOFTWARE LICENSE AGREEMENT ENCLOSED AT THE BACK OF THIS DOCUMENTATION.

Restricted Rights Legend

U.S. GOVERNMENT RESTRICTED RIGHTS. UNPUBLISHED -- RIGHTS RESERVED UNDER THE COPYRIGHT LAWS OF THE UNITED STATES. Use, duplication, or disclosure by the U.S. Government is subject to restrictions set forth in FAR Section 52.227-14 Alt. III (g)(3), FAR Section 52.227-19, DFARS 252.227-7014 (b) or DFARS 227.7202, as amended from time to time. Contractor/Manufacturer is BMC Software, Inc., 2101 CityWest Blvd., Houston, TX 77042-2827, USA. Any contract notices should be sent to this address.

Contacting BMC Software

You can access the BMC Software Web site at <http://www.bmc.com>. From this Web site, you can obtain information about the company, its products, corporate offices, special events, and career opportunities.

United States and Canada

Address BMC Software, Inc.
2101 CityWest Blvd.
Houston TX 77042-2827

Telephone 713 918 8800 or
800 841 2031

Fax 713 918 8000

Outside United States and Canada

Telephone (01) 713 918 8800

Fax (01) 713 918 8000

Customer Support

You can obtain technical support by using the Support page on the BMC Software Web site or by contacting Customer Support by telephone or e-mail. To expedite your inquiry, please see “Before Contacting BMC Software.”

Support Web Site

You can obtain technical support from BMC Software 24 hours a day, 7 days a week at <http://www.bmc.com/support.html>. From this Web site, you can

- read overviews about support services and programs that BMC Software offers
- find the most current information about BMC Software products
- search a database for problems similar to yours and possible solutions
- order or download product documentation
- report a problem or ask a question
- subscribe to receive e-mail notices when new product versions are released
- find worldwide BMC Software support center locations and contact information, including e-mail addresses, fax numbers, and telephone numbers

Support by Telephone or E-mail

In the United States and Canada, if you need technical support and do not have access to the Web, call 800 537 1813. Outside the United States and Canada, please contact your local support center for assistance. To find telephone and e-mail contact information for the BMC Software support center that services your location, refer to the Contact Customer Support section of the Support page on the BMC Software Web site at www.bmc.com/support.html.

Before Contacting BMC Software

Before you contact BMC Software, have the following information available so that Customer Support can begin working on your problem immediately:

- product information
 - product name
 - product version (release number)
 - license number and password (trial or permanent)
- operating system and environment information
 - machine type
 - operating system type, version, and service pack or other maintenance level such as PUT or PTF
 - system hardware configuration
 - serial numbers
 - related software (database, application, and communication) including type, version, and service pack or maintenance level
- sequence of events leading to the problem
- commands and options that you used
- messages received (and the time and date that you received them)
 - product error messages
 - messages from the operating system, such as `file system full`
 - messages from related software

Contents

About This Book	xi
Summary of Changes	xvii
Chapter 1	Introduction
	Overview..... 1-2
	Features and Functions..... 1-2
	Architecture 1-3
	Installation 1-4
	Requirements 1-4
	License Key 1-4
	HFS Component Directory and QM Profile 1-4
	Requirements for Monitoring DS Environments 1-5
	Starting the Node Manager for MQ 1-5
	Security Authorization 1-6
Chapter 2	Easy Menus and Views
	Overview..... 2-2
	MAINVIEW for WebSphere MQ Integrator Easy Menus 2-2
	EZMQI..... 2-2
	EZISSI 2-4
	MAINVIEW for WebSphere MQ Integrator Views 2-5
	WMQI Components List View..... 2-6
	Message Broker Views..... 2-7
	Execution Group Views 2-9
	Message Flow Views 2-10
	Message Flow Node Views 2-12
	Configuration Manager Views 2-13
	User Name Server Views 2-14
	Event Views 2-16
Chapter 3	Using MAINVIEW for WebSphere MQ Integrator
	Accessing MAINVIEW for WebSphere MQ Integrator 3-2
	Displaying the Components List 3-5

	Monitoring WMQI Components	3-7
	Displaying and Changing Component Properties.	3-8
	Starting and Stopping Components	3-10
	Running Traces	3-11
	Viewing Windows Application Events	3-13
	Exiting from MAINVIEW for WebSphere MQ Integrator.	3-16
Chapter 4	Setting Alarms	
	MAINVIEW Alarm Manager	4-2
	MAINVIEW for WebSphere MQ Integrator Alarms	4-2
Glossary		
Index		

Figures

Figure 1-1	MAINVIEW for WebSphere MQ Integrator Architecture	1-3
Figure 2-1	EZMQI Easy Menu	2-3
Figure 2-2	WMQI Components List (WMQICOMP) View	2-7
Figure 2-3	WMQI Broker Detail (BROKERD) View	2-8
Figure 2-4	WMQI Execution Group Trace (EGTRACE) View	2-10
Figure 2-5	WMQI Message Flow Detail (MSGFLOWD) View	2-11
Figure 2-6	WMQI Message Flow Node Detail (NODED) View	2-13
Figure 2-7	WMQI Configuration Manager Detail (CFGMGRD) View	2-14
Figure 2-8	WMQI User Name Server Overview (UNSVR) View	2-15
Figure 2-9	WMQI Event (EVTSQ) View	2-17
Figure 3-1	Session Control Parameters Panel	3-3
Figure 3-2	EZMQI Menu	3-4
Figure 3-3	WMQI Components List	3-5
Figure 3-4	WMQI Broker Details	3-9
Figure 3-5	WMQI Event Sources	3-13
Figure 3-6	WMQI Events List	3-14
Figure 3-7	WMQI Event Details	3-15

Tables

Table 2-1	Easy Menu Symbols	2-2
Table 2-2	EZMQI Easy Menu Categories	2-3
Table 2-3	List of MAINVIEW for WebSphere MQ Integrator Views	2-5
Table 2-4	Message Broker Views	2-7
Table 2-5	Execution Group Views	2-9
Table 2-6	Message Flow Views	2-11
Table 2-7	Message Flow Node Views	2-12
Table 2-8	Configuration Manager Views	2-13
Table 2-9	User Name Server Views	2-15
Table 2-10	Event Views	2-16

About This Book

This book contains detailed information about MAINVIEW for WebSphere MQ Integrator and is intended for network administrators and system administrators.

To use this book, you should be familiar with the following items:

- IBM's WebSphere MQ Integrator
- Multiple Virtual Storage (MVS) systems, job control language (JCL), and the Interactive System Productivity Facility (ISPF)
- your client and host operating systems

For example, you should know how to respond to ISPF panels and how to perform common actions in a window environment (such as choosing menu items and resizing windows).

How This Book Is Organized

This book is organized as follows.

Chapter/Appendix	Description
Chapter 1, "Introduction"	provides an introduction to the features and functions of MAINVIEW for WebSphere MQ Integrator
Chapter 2, "Easy Menus and Views"	explains the EZMQI and EZISSI Easy Menus and the MAINVIEW for WebSphere MQ Integrator views that are displayed on the MAINVIEW console

Chapter/Appendix	Description
Chapter 4, "Using MAINVIEW for WebSphere MQ Integrator"	provides instructions for using MAINVIEW for WebSphere MQ Integrator
Chapter 5, "Setting Alarms"	provides information about alarms in MAINVIEW for WebSphere MQ Integrator

In addition, this book contains a glossary of terms and an index.

Related Documentation

BMC Software products are supported by several types of documentation:

- online and printed books
- online Help
- release notes and other notices

In addition to this book and the Help, you can find useful information in the publications listed in the following table. As "Online and Printed Books" on page xiii explains, these publications are available on request from BMC Software.

Category	Document	Description
installation documents	<i>OS/390 and z/OS Installer Guide</i>	provides instructions for using the installation system, and describes the Product Authorization utility and AutoCustomization
	<i>MAINVIEW Installation Requirements Guide</i>	provides product-specific information such as software and storage requirements, product libraries, and FMIDs
	<i>Implementing Security for MAINVIEW Products</i>	provides information on basic MAINVIEW security, enhanced security, and MAINVIEW alternate access security
	<i>MAINVIEW Common Customization Guide</i>	provides instructions for manually customizing the MAINVIEW environment for your products
core documents	<i>MAINVIEW Administration Guide</i>	provides information about MAINVIEW operations, targets, single-system image contexts, MAINVIEW Alarm Manager, data sets, view customization, and diagnostic facilities
	<i>MAINVIEW Alarm Manager User Guide</i>	describes how to create and install alarm definitions that indicate when exceptions occur in a sysplex

Category	Document	Description
	<i>MAINVIEW Alternate Access Implementation and User Guide</i>	provides information on how to configure, start, and stop VTAM and EXCP AutoLogon sessions to access MAINVIEW products without an active TSO subsystem
	<i>MAINVIEW Explorer Implementation and User Guide</i>	describes how to install and use the host server and client software to access MAINVIEW products from a Web browser
	<i>MAINVIEW Quick Reference</i>	introduces the MAINVIEW family of products and lists the commands used to manage the MAINVIEW windows environment
	<i>Using MAINVIEW</i>	provides information about working with MAINVIEW products in windows mode and full-screen mode
supplemental documents	release notes, flashes, technical bulletins	provides current information about MAINVIEW for WebSphere MQ Integrator

Online and Printed Books

The books that accompany BMC Software products are available in online format and printed format. If you are a Windows or Unix user, you can view online books with Acrobat Reader from Adobe Systems. The reader is provided at no cost, as explained in “To Access Online Books.” You can also obtain additional printed books from BMC Software, as explained in “To Request Additional Printed Books.”

To Access Online Books

Online books are formatted as Portable Document Format (PDF) files. You can view them, print them, or copy them to your computer by using Acrobat Reader 3.0 or later. You can access online books from the documentation compact disk (CD) that accompanies your product or from the World Wide Web.

In some cases, installing the Acrobat Reader and downloading the online books is an optional part of the product-installation process. For information about downloading the free reader from the Web, go to the Adobe Systems site at <http://www.adobe.com>.

To view any online book that BMC Software offers, visit the Support page of the BMC Software Web site at <http://www.bmc.com/support.html>. Select a product to access the related documentation. (To log on, first-time users can request a user name and password by registering at the support page or by contacting a BMC Software sales representative.)

To Request Additional Printed Books

BMC Software provides some printed books with your product order. To request additional books, go to <http://www.bmc.com/support.html>.

Online Help

MAINVIEW for WebSphere MQ Integrator includes online Help. In the MAINVIEW for WebSphere MQ Integrator ISPF interface, you can access Help by pressing **F1** from any ISPF panel.

Release Notes and Other Notices

Printed release notes accompany each BMC Software product. Release notes provide current information such as

- updates to the installation instructions
- last-minute product information

In addition, BMC Software sometimes provides updated product information between releases (in the form of a flash or a technical bulletin, for example). The latest versions of the release notes and other notices are available on the Web at <http://www.bmc.com/support.html>.

Conventions

This section provides examples of the conventions used in this book and explains how to read ISPF panel-flow diagrams and syntax statements.

General Conventions

This book uses the following general conventions:

Item	Example
information that you are instructed to type	Type SEARCH DB in the designated field. Type search db in the designated field. (Unix)
specific (standard) keyboard key names	Press Enter .
GUI elements and menu sequences	Choose File => Open .
directories, file names, Web addresses, e-mail addresses	The BMC Software home page is at www.bmc.com .
Unix commands, command options, database names	Use the sbacktrack program to create a backup script.
code examples, syntax statements, system messages, screen text	//STEPLIB DD The table <i>tableName</i> is not available.
emphasized words, new terms	The instructions that you give to the software are called <i>commands</i> .
variables	In this message, the variable <i>fileName</i> represents the file that caused the error.

This book uses the following types of special text:

Note: Notes contain important information that you should consider.

Warning! Warnings alert you to situations that could cause problems, such as loss of data, if you do not follow instructions carefully.

Tip: Tips contain information that might improve product performance or that might make procedures easier to follow.

Syntax Statements

Syntax statements appear in Courier. The following example shows a sample syntax statement:

```
COMMAND KEYWORD1 [KEYWORD2|KEYWORD3] KEYWORD4={YES|NO}
    fileName...
```

The following table explains conventions for syntax statements and provides examples:

Item	Example
Items in italic type represent variables that you must replace with a name or value. If a variable is represented by two or more words, initial capitals distinguish the second and subsequent words.	<i>alias</i> <i>databaseDirectory</i>
Brackets indicate a group of options. You can choose at least one of the items in the group, but none of them is required. Do not type the brackets when you enter the option. A comma means that you can choose one or more of the listed options. You must use a comma to separate the options if you choose more than one option. Unix options are indicated with a hyphen.	[<i>tableName</i> , <i>columnName</i> , <i>field</i>] [-full, -incremental, -level] (Unix)
Braces enclose a list of required items. You must enter at least one of the items. Do not type the braces when you enter the item.	{ <i>DBDName</i> <i>tableName</i> } {-a -c} (Unix)
A vertical bar means that you can choose only one of the listed items. In the example, you would choose either <i>commit</i> or <i>cancel</i> .	{commit cancel} {-commit -cancel} (Unix)
An ellipsis indicates that you can repeat the previous item or items as many times as necessary.	<i>columnName</i> . . .

Summary of Changes

This section summarizes changes to the functionality of the product, listing the changes by product version and release date. The summary includes enhancements to the product and any major changes to the documentation.

Version 4.1

July 15, 2002

Initial release of the product.

Chapter 1 Introduction

This chapter contains the following sections:

Overview	1-2
Features and Functions	1-2
Architecture	1-3
Installation	1-4
Requirements	1-4
License Key	1-4
HFS Component Directory and QM Profile	1-4
Requirements for Monitoring DS Environments	1-5
Starting the Node Manager for MQ	1-5
Security Authorization	1-6

Overview

MAINVIEW® for WebSphere MQ Integrator is a system management application that provides services and functions that help you monitor and manage your IBM WebSphere MQ Integrator (WMQI) network. This product allows you to monitor components using multiple panels of different sizes simultaneously and to direct actions from one panel to another, all on one terminal. This product also allows you to start and stop traces for multiple brokers and broker resources easily from one location.

Built on the BMC Software MAINVIEW architecture, MAINVIEW for WebSphere MQ Integrator uses a traditional MAINVIEW interface to provide access to broker network information. For more information on the MAINVIEW architecture, how to navigate in MAINVIEW, and how to customize MAINVIEW views, see *Using MAINVIEW*.

MAINVIEW for WebSphere MQ Integrator is a licensed feature of MAINVIEW for WebSphere MQ and requires this product as a prerequisite.

Features and Functions

MAINVIEW for WebSphere MQ Integrator displays information for WMQI components that are hosted by the target queue manager. You can display WMQI component information for a single queue manager or for all of the queue managers in the current context using Single System Image (SSI) mode. For information on setting contexts, see the sections on displaying target systems and SSI contexts in *Using MAINVIEW*.

This release of MAINVIEW for WebSphere MQ Integrator contains the following features and functions:


- provides a queue manager based view of WMQI components
- discovers WMQI components automatically
- monitors OS/390, Unix, and Windows broker networks
- displays properties and real-time status of WMQI components and their resources, including message flow nodes and associated queues
- provides information on OS/390 broker and user name server address spaces
- allows you to change properties and to start and stop WMQI components and their resources

- allows you to start and stop traces and change trace attributes
- displays Windows application events

Architecture

MAINVIEW for WebSphere MQ Integrator is a licensed feature of MAINVIEW for WebSphere MQ and runs in the same BBI-PAS address space. Figure 1-1 illustrates how MAINVIEW for WebSphere MQ Integrator communicates with WMQI on OS/390 and Distributed Systems.

Figure 1-1 MAINVIEW for WebSphere MQ Integrator Architecture



On OS/390, MAINVIEW for WebSphere MQ Integrator communicates with WMQI components through the PAS. On Distributed Systems, PATROL for WebSphere MQ Integrator uses the Node Manager for MQ to pass information between WMQI components and the PAS. To monitor WMQI components on Distributed Systems, you must install PATROL for WebSphere MQ Integrator on each host that you want to monitor.

Installation

MAINVIEW for WebSphere MQ Integrator is installed when you install MAINVIEW for WebSphere MQ. See the *MAINVIEW for WebSphere MQ User Guide* for information on installing that product. The remainder of this section contains installation requirements and post-installation tasks.

Requirements

The following products are required to run MAINVIEW for WebSphere MQ Integrator:

- WebSphere MQ Integrator for z/OS 2.1
- MAINVIEW for WebSphere MQ 4.1
- PATROL for WebSphere MQ Integrator 1.3.02, if you are monitoring Distributed Systems components

License Key

When you have installed MAINVIEW for WebSphere MQ, you will need a license key to access MAINVIEW for WebSphere MQ Integrator and MAINVIEW for WebSphere MQ. Contact your BMC Software Sales Representative to obtain the license key.

HFS Component Directory and QM Profile

You must set a target for each queue manager associated with components that you want to monitor. See the *MAINVIEW for WebSphere MQ User Guide* for instructions on setting a target by defining queue manager profiles.

To monitor WMQI components, you must complete the following WMQI Extensions options as part of the profile on the QMPROF view:

- Broker Directory
- UNS Directory

Fill in the HFS component directory path for the components (broker and/or user name server) hosted by the queue manager. The path corresponds to the value of the COHFS parameter in the respective broker or user name server started task.

Requirements for Monitoring DS Environments

To monitor WMQI components on Distributed Systems, you must install PATROL for WebSphere MQ Integrator on each host that you want to monitor. The PATROL Agent is not required nor used to monitor Distributed Systems components from MAINVIEW for WebSphere MQ Integrator. The Node Manager for MQ, installed with PATROL for WebSphere MQ Integrator, communicates information between WMQI components on Distributed Systems and the PAS.

Starting the Node Manager for MQ

After you install PATROL for WebSphere MQ Integrator on each Distributed Systems host that you want to monitor, you must start the Node Manager for MQ. Run the following command from your operating console to install the Node Manager for MQ and start communications with MAINVIEW for WebSphere MQ Integrator:

Platform	Command
Windows	MCMNM -install
Unix	MCMNM

The Node Manager for MQ port defaults to 5000. To change the default port, add the following parameter to the MCMNM command:

`-s <port number>`

The Node Manager for MQ runs as a service on Windows. It is not supported on the Windows 95 platform.

Security Authorization

Proper access must be enabled for communication between MAINVIEW for WebSphere MQ Integrator and WebSphere MQ Integrator. The following is required for proper authorization:

- in RACF, the PAS user ID must have an OMVS segment with UID = 0
- MAINVIEW for WebSphere MQ Integrator must have PUT authority access to the **SYSTEM.BROKER.*** queue
- to monitor WMQI components on Distributed Systems, the user ID used to install PATROL for WebSphere MQ Integrator must be a member of the **mqm** and **mqbrkrs** MQSeries groups

For further information on security, see the following:

- *Implementing Security for MAINVIEW Products*
- *PATROL for WebSphere MQ Integrator User Guide*
- *WebSphere MQ Integrator for z/OS Customization and Administration Guide*

Chapter 2 Easy Menus and Views

This chapter contains the following sections:

Overview	2-2
MAINVIEW for WebSphere MQ Integrator Easy Menus	2-2
EZMQI	2-2
EZISSI	2-4
MAINVIEW for WebSphere MQ Integrator Views	2-5
WMQI Components List View	2-6
Message Broker Views	2-7
Execution Group Views	2-9
Message Flow Views	2-10
Message Flow Node Views	2-12
Configuration Manager Views	2-13
User Name Server Views	2-14
Event Views	2-16

Overview

MAINVIEW for WebSphere MQ Integrator views display information that helps you monitor and manage your broker network. Easy menus provide a convenient way to use MAINVIEW for WebSphere MQ Integrator without having to remember view names.

MAINVIEW for WebSphere MQ Integrator Easy Menus

Easy menus allow you to navigate through the product based on a feature you want to monitor rather than on a specific view. There are two easy menus in MAINVIEW for WebSphere MQ Integrator: EZMQI and EZISSI.

Easy menus have symbols to the left of the hyperlinks to indicate certain actions. Table 2-1 describes symbols that are used in easy menus.

Table 2-1 **Easy Menu Symbols**

Symbol	Description
>	takes you to another easy menu (sub-menu)
.	takes you directly to a view that displays data

EZMQI

EZMQI is the primary easy menu for MAINVIEW for WebSphere MQ Integrator. The selections on this menu let you access product views for a specified target quickly. For example, you can access broker details for a specified queue manager from this menu.

Figure 2-1 shows the EZMQI easy menu.

Figure 2-1 EZMQI Easy Menu

```

01JUL2002 15:05:39 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>
CURR WIN ==> 1          ALT WIN ==>
>W1 =EZMQI=====CMQM=====*=====01JUL2002==15:05:39====MVMQS====D====1
                                Message Broker Menu

Qmgr Target Name --->  CMQM                                cmqm
WMQI Components
. All Components          +-----+ > Tools and Menus
. Message Broker          | Place cursor on | > Change Context
. Config Manager          | menu item and  | > Select View
. User Name Server        | press ENTER   | . Queue Manager Profile
> MVS Only Resources      +-----+ . Audit and Message Log

Msg Broker Resources      Trace settings                    Queues Summary
. Execution Groups        . Message Broker trace          . Per Message Broker
. Message Flows           . Execution Groups trace        . Per Execution Group
. Nodes                  . Message Flows trace           . Per Message Flow
                          . User Name Server trace

Events
. Event Sources           WebSphere MQ feature
                          > Queue Manager Menu
                          . Return

```

Options on this menu are grouped into the categories described in Table 2-2.

Table 2-2 EZMQI Easy Menu Categories

Category	Description
WMQI Components	links to views of all components, brokers, the configuration manager, and the user name server
Message Broker Components	links to views of execution groups, message flows, and nodes
Events	links to views of event sources, events, and event details
Trace Settings	links to views of broker, execution group, message flow, and user name server trace settings
Tools and Menus	links to sub-menus for changing the context and displaying all views, and to the queue manager profile and audit and message log
Queues Summary	links to a queue summary per broker, per execution group, or per message flow
WebSphere MQ Feature	links to the queue manager sub-menu

EZISSI

The EZISSI easy menu provides access to views for multiple targets. For example, you can access broker details for all of the queue managers with associated brokers from this menu. Options on this menu are grouped in the same categories as the EZMQI menu.

You can display the EZISSI menu by typing **EZISSI** on the Command Line and pressing **Enter**.

MAINVIEW for WebSphere MQ Integrator Views

MAINVIEW for WebSphere MQ Integrator views display information that helps you monitor and manage your WMQI broker network. You can display views and manage panels in MAINVIEW for WebSphere MQ Integrator the same way you do in any MAINVIEW product. You can display multiple panels of different sizes simultaneously and you can direct actions from one panel to another, all on one terminal.

In several views, you can perform a “drill-down” function. Drill-down functions let you view more detailed information about an item. You can drill down for more information in any view where a field name is highlighted. Some highlighted field names are hyperlinks to other applications or resources. For sample instructions on how to perform a drill-down function, see “Monitoring WMQI Components” on page 3-7.

To display a list of all MAINVIEW for WebSphere MQ Integrator views, select **Select View** from Tools and Menus on the EZMQI menu and press **Enter**. Table 2-3 lists all of the MAINVIEW for WebSphere MQ Integrator views. The remainder of this chapter discusses these views in more detail.

Table 2-3 **List of MAINVIEW for WebSphere MQ Integrator Views (Part 1 of 2)**

View	Name
WMQICOMP	WMQI Components List
BROKER	WMQI Broker Overview
BROKERD	WMQI Broker Detail
BKRZOS	WMQI z/OS Broker Overview
BKRZOSD	WMQI z/OS Broker Detail
MBTRACE	WMQI Broker Trace
EXECGRP	WMQI Execution Group Overview
EXECGRPD	WMQI Execution Group Detail
EGTRACE	WMQI Execution Group Trace
MSGFLOW	WMQI Message Flow Overview
MSGFLOWD	WMQI Message Flow Detail
MFTRACE	WMQI Message Flow Trace
NODE	WMQI Message Flow Node Overview
NODEZ	WMQI Message Flow Node Summary
NODED	WMQI Message Flow Node Detail
MBQZ	WMQI Broker Queues Summary
MBQS	WMQI Broker Queues

Table 2-3 **List of MAINVIEW for WebSphere MQ Integrator Views
(Part 2 of 2)**

View	Name
EGQZ	WMQI Execution Group Queues Summary
EGQS	WMQI Execution Group Queues
MFQZ	WMQI Message Flow Queues Summary
MFQS	WMQI Message Flow Queues
CFGMGR	WMQI Configuration Manager Overview
CFGMGRD	WMQI Configuration Manager Detail
UNSVR	WMQI User Name Server Overview
UNSVRD	WMQI User Name Server Detail
UNSZOS	WMQI z/OS User Name Server Overview
UNSZOSD	WMQI z/OS User Name Server Detail
UNTRACE	WMQI User Name Server Trace
EVTs	WMQI Event Sources
EVTZQ	WMQI Event Browse
EVTsQ	WMQI Event
EVTsQD	WMQI Event Details

WMQI Components List View

The WMQI Components List (WMQICOMP) view provides information on all of the WMQI components associated with a queue manager or group of queue managers, depending on your target setting. This view displays the component name, the type of component, current status of the component (running or stopped), and the queue manager name and context for each component.

Figure 2-2 shows the WMQI Components List view.

Figure 2-2 WMQI Components List (WMQICOMP) View

```

01JUL2002 15:27:11 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>
CURR WIN ==> 1          ALT WIN ==>
>W1 =WMQICOMP=====CMQM=====*=====01JUL2002==15:27:10====MVMQS====D====2
CMD Component                                Comp Comp  QueueManager      QMgr
--- Name                                     Type Status  Name              Contex
ConfigMgr                                   CMR  Running cmqm      CMQM
UserNameServer                             UNS  Running cmqm      CMQM

```

Message Broker Views

Message broker views provide status, resource, property, and trace information for brokers associated with active queue managers. From the broker overview, you can monitor broker availability and drill-down to views for associated resources. You can change broker properties using the detail views and change trace attributes using the trace view. You can also start and stop WMQI components from the broker views.

Table 2-4 describes the views that provide detailed information about message brokers.

Table 2-4 Message Broker Views (Part 1 of 2)

View	Description
BROKER	The WMQI Broker Overview view displays name, status, platform type, resources, and the associated queue manager name for each broker. You can drill-down to resources and start and stop them from this view.
BROKERD	The WMQI Broker Detail view displays broker properties, such as the UUID, Process ID, status, data source name, user LIL path, and number of resources.

Table 2-4 Message Broker Views (Part 2 of 2)

View	Description
BKRZOS	The WMQI z/OS Broker Overview view displays the address space and type of address space where each broker is running, in addition to the name and resources of each OS/390 broker. You can drill down to resources and start and stop them from this view.
BKRZOSD	The WMQI z/OS Broker Detail view displays broker address space properties, USS process information including the HFS path name, the UUID, and resource information for an OS/390 broker.
MBTRACE	The WMQI Broker Trace view displays all trace settings for the current broker context, both active and inactive. You can start and stop traces and change trace attributes from this view.

Figure 2-3 shows the WMQI Broker Detail view.

Figure 2-3 WMQI Broker Detail (BROKERD) View

```

01JUL2002 16:15:12 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>                                SCROLL ==> CSR
CURR WIN ==> 1          ALT WIN ==>
>W1 =BROKER==BROKERD==HNBKR====*=====01JUL2002==16:14:58===MVMQS===D===1
Broker Properties.....
Broker Name..... HUYNHMB
Broker UUID..... a5923832-dd00-0000-0080-ab4b84e10d89
Broker Process Id..... 700
Broker Status..... Running

Configuration Timeout..... 300
Configuration Delay Timeout. 60
Service User Id..... .\patrol
Service User Password..... *****
Data Source Name..... MQSIBKDB
Data Source User ID..... patrol
Data Source User Password... *****
User Name Server QMgr..... (None)
Work Path..... (None)
User LIL Path..... D:/Program Files/IBM/WebSphere MQ Integrator
                2.1/bin;D:/Program Files/IBM/WebSphere MQ I
                ntegrator 2.1/jplugin

MQSeries Trusted Application no
Migrate Pub/Sub Broker..... no

```

Execution Group Views

Execution group views provide status, resource, property, and trace information for execution groups. From the execution group overview, you can monitor execution group availability and drill-down to views for associated resources. You can change execution group properties using the detail view and change trace attributes using the trace view.

You can start and stop resources from these views; however, you cannot start or stop execution groups. This must be done at the broker level.

Table 2-5 describes the views that provide detailed information about execution groups.

Table 2-5 Execution Group Views

View	Description
EXECGRP	The WMQI Execution Group Overview view displays name, trace status, resources, and the associated broker for each execution group. You can drill-down to resources and start and stop them from this view.
EXECGRPD	The WMQI Execution Group Detail view displays execution group properties, such as the UUID, trace levels, the associated broker, and the number of started and stopped message flows.
EGTRACE	The WMQI Execution Group Trace view displays all trace settings, both active and inactive, for the listed execution groups. You can start and stop traces and change trace attributes from this view.

Figure 2-4 shows the WMQI Execution Group Trace view.

Figure 2-4 WMQI Execution Group Trace (EGTRACE) View

```

01JUL2002 16:22:22 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>
CURR WIN ==> 1          ALT WIN ==>
>W1 =EGTRACE=====HNBKR====*=====01JUL2002==16:21:44===MVMQS===D===2
CMD Execution          ----- User Trace-- ---Ser vice Trace-- Trace Brok
--- Group              Level  Mode Size   Level  Mode Size   Reset Name
  default              none   safe   4096 none   safe   4096 yes   HUYN
  WMQIEG1              none   safe   4096 none   safe   4096 yes   HUYN

```

Message Flow Views

Message flow views provide status, property, and trace information for message flows. From the message flow overview, you can monitor the status of message flows and traces. You can change message flow properties using the detail view and change trace attributes using the trace view. You can start and stop message flows from these views.

Table 2-6 describes the views that provide detailed information about message flows.

Table 2-6 Message Flow Views

View	Description
MSGFLOW	The WMQI Message Flow Overview view displays name, status, trace status, and the associated execution group and broker for each message flow.
MSGFLOWD	The WMQI Message Flow Detail view displays message flow properties, such as the UUID, trace levels, and the associated execution group and broker. You can drill down to node information from this view.
MFTRACE	The WMQI Message Flow Trace view displays all trace settings, both active and inactive, for the listed message flows. You can start and stop traces and change trace attributes from this view.

Figure 2-5 shows the WMQI Message Flow Detail view.

Figure 2-5 WMQI Message Flow Detail (MSGFLOWD) View

```

01JUL2002 16:24:14 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>                                     SCROLL ==> CSR
CURR WIN ==> 1          ALT WIN ==>
>W1 =MSGFLOW=MSGFLOWD=HNBKR====*=====01JUL2002==16:23:56====MVMQS====D====1
  Message Flow Properties.....
    Message Flow Name..... mfl
    Message Flow UUID..... 49266927-ee00-0000-0080-cb1c88520498
    Message Flow Status..... Started
    User Trace Level..... none
      User Trace Mode..... safe
      User Trace Size..... 4096
    Service Trace Level..... none
      Service Trace Mode..... safe
      Service Trace Size..... 4096
    Trace Log Reset..... yes
    User Trace Filter..... None
    Additional Instances..... 0
    Commit Count..... 1
    Commit Interval..... 0
    Coordinated Transaction..... No

    <Message Flow Nodes>.....
    <Message Flow In-Out Queues>

```

Message Flow Node Views

Message flow node views provide node type, property, and queue information for message flow nodes. From the message flow node overview, you can access the node type and message flow to which the node belongs. You can access node properties using the detail view. The queues and queue summary views provide the count of input and output nodes for a given context and the queues for each node associated with a component.

Table 2-7 describes the views that provide detailed information about message flow nodes.

Table 2-7 Message Flow Node Views

View	Description
NODE	The WMQI Message Flow Node Overview view lists node information, including the node name, type of node, and message flow to which the node belongs.
NODEZ	The WMQI Message Flow Node Summary view displays a list of node types used by the message flows in the current context and the count of each node type.
NODED	The WMQI Message Flow Node Detail view displays node properties such as the node type, UUID, trace level, and out, failure, and catch terminal connections.
MBQZ	The WMQI Broker Queues Summary view displays the count of input and output queues for the listed broker context.
MBQS	The WMQI Broker Queues view displays the queues for each node under a broker. The execution group and message flow are also listed for each node queue name.
EGQZ	The WMQI Execution Group Queues Summary view displays the count of input and output queues for each execution group.
EGQS	The WMQI Execution Group Queues view displays the queues for each node under an execution group. The message flow and broker are also listed for each node queue name.
MFQZ	The WMQI Message Flow Queues Summary view displays the count of input and output queues for each message flow in a context, in addition to the execution group name and broker name for each message flow.
MFQS	The WMQI Message Flow Queues view displays the queues for each node under a message flow. The execution group and broker are also listed for each node queue name.

Figure 2-6 shows the WMQI Message Flow Node Detail view.

Figure 2-6 WMQI Message Flow Node Detail (NODED) View

```

01JUL2002 16:25:07 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>
CURR WIN ==> 1          ALT WIN ==>
>W1 =NODED=====HNBKR====*=====01JUL2002==16:25:06====MVMQS====D====1
Message Flow Node Properties
Attribute Name                                Attribute Value
type                                           ComIbmMQInputNode
name                                           mfl_in4
uuid                                           c2ea6927-ee00-0000-0080-cb1c885204
userTraceLevel                               none
traceLevel                                   none
userTraceFilter                              none
traceFilter                                  none
label                                          mfl_in4
messageDomainProperty                        XML
queueName                                    mfl_in4
transactionMode                             yes
orderMode                                    default
logicalOrder                                yes
allMsgsAvailable                            no
matchMsgId                                  no
matchCorrelId                               no
convert                                      no
convertEncoding                              546

```

Configuration Manager Views

Configuration manager views provide status and property information for the configuration manager. From the configuration manager overview, you can monitor the status of the configuration manager and its associated queue manager. You can change configuration manager properties and start or stop the configuration manager using the detail view.

Table 2-8 describes the views that provide detailed information about the configuration manager.

Table 2-8 Configuration Manager Views

View	Description
CFGMGR	The WMQI Configuration Manager Overview view displays the name, status, PID, and platform for the configuration manager. This view also displays the name and status of the queue manager associated with the configuration manager.
CFGMGRD	The WMQI Configuration Manager Detail view displays configuration manager properties, such as the Process ID, status, data source name, work path, and associated queue manager.

Figure 2-7 shows the WMQI Configuration Manager Detail view.

Figure 2-7 WMQI Configuration Manager Detail (CFGMGRD) View

```

01JUL2002 15:46:11 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>
CURR WIN ==> 1          ALT WIN ==>
>W1 =CFGMGRD=====CMQM=====*=====01JUL2002==15:46:10===MVMQS===D===1
  ConfigMgr Properties.....
    ConfigMgr Name..... ConfigMgr
    ConfigMgr Process Id..... 840
    ConfigMgr Status..... Running

    Service User Id..... .\patrol
    Service User Password..... *****
    Data Source Name..... MQSICMDB
    Data Source User ID..... patrol
    Data Source User Password... *****
    JDBC Connection Name..... db2
    JDBC Driver Name..... COM.ibm.db2.jdbc.app.DB2Driver
    MRM Data Source Name..... MQSIMRDB
    MRM Data Source User ID..... patrol
    MRM Data Source User Password *****
    NT Security Domain.....
    User Name Server QMgr.....
    Work Path.....

    Queue Manager..... cmqm

```

User Name Server Views

User name server views provide status, property, and trace information for the user name server. From the user name server overview, you can monitor the status of the user name server and its associated queue manager. You can change user name server properties and start or stop the user name server using the detail view. You can change trace attributes using the trace view.

Table 2-9 describes the views that provide detailed information about the user name server.

Table 2-9 User Name Server Views

View	Description
UNSVR	The WMQI User Name Server Overview view displays the name, status, PID, and platform for the user name server. This view also displays the name and status of the queue manager associated with the user name server.
UNSVRD	The WMQI User Name Server Detail view displays user name server properties, such as the Process ID, status, service user ID, work path, and associated queue manager.
UNSZOS	The WMQI z/OS User Name Server Overview view displays the address space and type of address space where the user name server is running.
UNSZOSD	The WMQI z/OS User Name Server Detail view displays user name server address space properties, USS process information including the HFS path name, and the UUID for the OS/390 user name server.
UNTRACE	The WMQI User Name Server Trace view displays all trace settings, both active and inactive, for the user name server. You can start and stop traces and change trace attributes from this view.

Figure 2-8 shows the WMQI User Name Server Overview view.

Figure 2-8 WMQI User Name Server Overview (UNSVR) View

```

01JUL2002 15:47:34 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>
CURR WIN ==> 1          ALT WIN ==>
>W1 =UNSVR=====CMQM=====*=====01JUL2002==15:47:24====MVMQS=====D=====1
CMD  UsrNamSvr      UsrNamSvr UsrNamSvr Platform QMgr      Queue Manager
--- Name           Status    PID      Type      Status    Name
   UserNameServer  Running   695      Win NT    Active    cmqm

```

Event Views

Event views display Windows NT application events and event details. From the event sources view, you can select applications for which you want to view events.

Table 2-10 describes the views that provide detailed information about event sources.

Table 2-10 Event Views

View	Description
EVTS	The WMQI Event Sources view displays the list of applications for which Windows NT events are logged. You can select applications from this list in order to view events generated by these applications.
EVTZQ	The WMQI Event Browse view is displayed when you select an application from the WMQI Event Sources (EVTS) view. The browse view allows you to specify a starting position or number of events to retrieve for a the selected application.
EVTSQ	WMQI Event view displays application events for the applications you selected. This view displays the event number, severity, date, time, event ID, and event source. You can select an event from this view to display further details.
EVTSQD	WMQI Event Details view displays details for a selected application event. This view displays the event source, number, identity, severity, date, time, and event description.

Figure 2-2 shows the WMQI Event view.

Figure 2-9 WMQI Event (EVTSQ) View

```

01JUL2002 16:07:35 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>
CURR WIN ==> 1          ALT WIN ==>
>W1 =EVTSQ=====CMQM=====01JUL2002==16:07:31====MVMQS====D===66
CMD      Event Event      Event      Event      Event      Event
---      Number Severity   Date       Time       Ident      Source
      2213 INFO      07/01/2002  02:19:52PM  9545    MQSeries
      2212 ERROR     07/01/2002  02:17:30PM  9999    MQSeries
      2211 ERROR     07/01/2002  02:17:30PM  9202    MQSeries
      2210 INFO      07/01/2002  02:17:28PM  9002    MQSeries
      2209 ERROR     07/01/2002  01:57:30PM  9999    MQSeries
      2208 ERROR     07/01/2002  01:57:30PM  9202    MQSeries
      2207 INFO      07/01/2002  01:57:28PM  9002    MQSeries
      2206 ERROR     07/01/2002  01:37:30PM  9999    MQSeries
      2205 ERROR     07/01/2002  01:37:30PM  9202    MQSeries
      2204 INFO      07/01/2002  01:37:28PM  9002    MQSeries
      2201 ERROR     07/01/2002  01:17:29PM  9999    MQSeries
      2200 ERROR     07/01/2002  01:17:29PM  9202    MQSeries
      2199 INFO      07/01/2002  01:17:27PM  9002    MQSeries
      2198 ERROR     07/01/2002  12:57:29PM  9999    MQSeries
      2197 ERROR     07/01/2002  12:57:29PM  9202    MQSeries
      2196 INFO      07/01/2002  12:57:27PM  9002    MQSeries
      2187 INFO      07/01/2002  12:39:42PM  9002    MQSeries
      2186 INFO      07/01/2002  12:39:41PM  9002    MQSeries

```

Chapter 3 Using MAINVIEW for WebSphere MQ Integrator

This chapter contains the following sections:

Accessing MAINVIEW for WebSphere MQ Integrator.	3-2
Displaying the Components List.	3-5
Monitoring WMQI Components	3-7
Displaying and Changing Component Properties.	3-8
Starting and Stopping Components	3-10
Running Traces	3-11
Viewing Windows Application Events	3-13
Exiting from MAINVIEW for WebSphere MQ Integrator.	3-16

Accessing MAINVIEW for WebSphere MQ Integrator

Summary: You can access MAINVIEW for WebSphere MQ Integrator from the MAINVIEW Selection Menu.

Before You Begin

You must have MAINVIEW for WebSphere MQ installed in order to access MAINVIEW for WebSphere MQ Integrator.

To Access the Product

- Step 1** Display the MAINVIEW Selection Menu.
- Step 2** Type **W** on the command line to select **WebSphere and MQSeries**, and press **Enter**.
- The WebSphere and MQSeries Solutions menu is displayed.
- Step 3** Type **2** on the command line to select **MAINVIEW for WebSphere MQ** (or **MAINVIEW for MQSeries** in some versions of the product), and press **Enter**.
- The WebSphere MQ Performance and Control menu is displayed.
- Step 4** Type **2** on the command line to select **MAINVIEW for WebSphere MQ Integrator**, and press **Enter**.
- The Session Control Parameters panel (Figure 3-1) is displayed.

Figure 3-1 Session Control Parameters Panel

```
BMC SOFTWARE ----- SESSION CONTROL PARAMETERS -----  
COMMAND ==>  
  
Subsystem ID    ==> BCLR    (CAS Subsystem ID, ? for list of active SSIDs)  
  
XDM mode        ==> NO      (Execute session in diagnostic mode, Yes/No)  
  
Press ENTER to confirm use of session parameters entered above.  
  
  
  
  
  
  
  
  
  
F1=HELP      F2=SPLIT    F3=END      F4=RETURN   F5=RFIND    F6=RCHANGE  
F7=UP        F8=DOWN     F9=SWAP    F10=LEFT   F11=RIGHT   F12=RETRIEVE
```

Step 5 Type the subsystem ID for the coordinating address space (CAS), and press **Enter**.

If you do not know the subsystem ID, see your MAINVIEW for WebSphere MQ Integrator administrator. The EZMQI Menu (Figure 3-2) is displayed.

Figure 3-2 EZMQI Menu

```

01JUL2002 16:13:15 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ===>
CURR WIN ===> 1          ALT WIN ===>
>W1 =EZMQI=====HNBKR====*=====01JUL2002==16:13:15===MVMQS===D===1
                                Message Broker Menu

Qmgr Target Name --->  HNBKR                                huynh
WMQI Components
. All Components          +-----+ > Change Context
. Message Broker          | Place cursor on | > Select View
. Config Manager          | menu item and  | . Queue Manager Profile
. User Name Server        | press ENTER   | . Audit and Message Log
> MVS Only Resources      +-----+

Msg Broker Resources      Trace settings                    Queues Summary
. Execution Groups        . Message Broker trace          . Per Message Broker
. Message Flows           . Execution Groups trace       . Per Execution Group
. Nodes                   . Message Flows trace          . Per Message Flow
                           . User Name Server trace

Events
. Event Sources           > Queue Manager Menu
                           . Return

```

Displaying the Components List

Summary: The components list displays information about all of the WMQI components associated with a single queue manager or all of the queue managers in the current context. You can quickly determine which components are running using this view. You can also drill-down to more detailed information about the components in the list.

To Display the WMQI Components List

Step 1 Set the context to the queue manager or queue managers for which you want to view WMQI components.

Step 2 From the EZMQI Easy Menu, select **All Components** and press **Enter**.

The WMQI Components List view (Figure 3-3) is displayed.

Note: You can also access this view by typing **WMQICOMP** on the command line and pressing **Enter**.

Figure 3-3 WMQI Components List

```
01JUL2002 16:14:12 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>
CURR WIN ==> 1          ALT WIN ==>
>W1 =WMQICOMP=====HNBKR=====*=====01JUL2002==16:14:11====MVMQS====D====1
CMD Component          Comp Comp   QueueManager          QMgr
--- Name              Type Status Name                  Contex
    HUYNHMB           BRK  Running huynh                HNBKR
```

Step 3 To display detailed information for a component, select the component and press **Enter**.

The detail view for the component is displayed.

Note: See the online help for further information on the commands available in this view.

Monitoring WMQI Components

Summary: You can monitor the status of brokers, execution groups, message flows, and the user name server on OS/390 and Distributed Systems.

This task provides an example of how to monitor execution groups and message flows. Once you determine which components you will monitor on a regular basis, you can save screens with the views that are the most useful. See *Using MAINVIEW* for instructions on saving screens with views.

To Monitor Execution Groups and Message Flows

Step 1 Set the context to the queue manager or queue managers for which you want to monitor execution groups and message flows.

Step 2 Type **EXECGRP** on the command line and press **Enter**.

The WMQI Execution Group Overview is displayed. From this view, you can determine the number of message flows that are started and stopped in each execution group and the trace status.

Step 3 To display detailed information for an execution group, select an execution group and press **Enter**.

The WMQI Execution Group Detail view is displayed.

Step 4 To check the status of individual message flows under this execution group, select the total count in the **Message Flows** field and press **Enter**.

The WMQI Message Flow Overview is displayed. From this view, you can determine which message flows are started or stopped.

Note: See the online help for further information on the commands available in these views.

Displaying and Changing Component Properties

Summary: You can display and change properties for brokers, execution groups, message flows, nodes, the configuration manager, and the user name server.

This task provides an example of how to change broker properties.

To Display and Change Broker Properties

Step 1 Set the context to the queue manager associated with the broker for which you want to change properties.

Step 2 Type **BROKER** on the command line and press **Enter**.

The WMQI Broker Overview is displayed. From this view, you can determine the status of the broker and the number of resources that are associated with it.

Step 3 To display detailed information for a broker, select the broker and press **Enter**.

The WMQI Broker Detail view (Figure 3-4) is displayed.

Figure 3-4 WMQI Broker Details

```

01JUL2002 16:15:12 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>                                SCROLL ==> CSR
CURR WIN ==> 1          ALT WIN ==>
>W1 =BROKER==BROKERD==HNBKR====*=====01JUL2002==16:14:58==MVMQS====D====1
Broker Properties.....
Broker Name..... HUYNHMB
Broker UUID..... a5923832-dd00-0000-0080-ab4b84e10d89
Broker Process Id..... 700
Broker Status..... Running

Configuration Timeout..... 300
Configuration Delay Timeout.. 60
Service User Id..... .\patrol
Service User Password..... *****
Data Source Name..... MQSIBKDB
Data Source User ID..... patrol
Data Source User Password... *****
User Name Server QMgr..... (None)
Work Path..... (None)
User LIL Path..... D:/Program Files/IBM/WebSphere MQ Integrator
                    2.1/bin;D:/Program Files/IBM/WebSphere MQ I
                    ntegrator 2.1/jplugin

MQSeries Trusted Application no
Migrate Pub/Sub Broker..... no

```

Step 4 To change properties, overtype the values in the fields you want to change and press **Enter**.

Properties are updated.

Note: See the online help for further information on the fields you can change in this view.

Starting and Stopping Components

Summary: You can start and stop brokers, message flows, the configuration manager, and the user name server. You can stop execution groups indirectly by stopping all of the message flows under the execution group, or by stopping the message broker for the execution group.

This task provides an example of how to start and stop a message flow.

To Start a Message Flow

Step 1 Set the context to the queue manager associated with the broker that contains the message flow you want to start.

Step 2 Type **MSFLOW** on the command line and press **Enter**.

The WMQI Message Flow Overview is displayed. This view allows you to check the current status of message flows.

Step 3 In the CMD column of the message flow you want to start, type **STA** and press **Enter**.

The message flow is started.

To Stop a Message Flow

Step 1 Set the context to the queue manager associated with the broker that contains the message flow you want to stop.

Step 2 Type **MSFLOW** on the command line and press **Enter**.

The WMQI Message Flow Overview is displayed. This view allows you to check the current status of message flows.

Step 3 In the CMD column of the message flow you want to stop, type **STO** and press **Enter**.

The message flow is stopped.

Running Traces

Summary: You can start and stop traces for brokers, execution groups, message flows, and the user name server using MAINVIEW for WebSphere MQ Integrator. You can also set trace attributes. To view trace data, you must use WebSphere MQ Integrator.

This task provides an example of how to run a trace on a message broker.

To Start a Broker Trace

Step 1 Set the context to the queue manager associated with the broker you want to start tracing.

Step 2 Type **MBTRACE** on the command line and press **Enter**.

The WMQI Broker Trace view is displayed.

Step 3 On the line for the broker you want to trace, overwrite the following fields as necessary to specify attributes for the trace:

Field	Values
Level	type normal to run a normal level trace type debug to run a more detailed trace
Mode	type safe to write trace information to a file as it is generated type fast to write trace information to a file in batches
Size	type a file size in kilobytes the trace file defaults to 1024 KB; you can enter a value up to 2 GB

Step 4 Press **Enter**.

The trace is started.

To Stop a Broker Trace

Step 1 Set the context to the queue manager associated with the broker you want to stop tracing.

Step 2 Type **MBTRACE** on the command line and press **Enter**.

The WMQI Broker Trace view is displayed.

Step 3 On the line for the broker you want to stop tracing, type **none** in the **Level** field.

The trace is stopped.

Viewing Windows Application Events

Summary: To view Windows application events, you must select an application (event source) for which you want to view events, then specify how you want the events displayed.

To View Events

Step 1 From the EZMQI Easy Menu, select **Event Sources** and press **Enter**.

The WMQI Event Sources view (Figure 3-5) is displayed.

Note: You can also access this view by typing **EVTS** on the command line and pressing **Enter**.

Figure 3-5 WMQI Event Sources

```
01JUL2002 16:03:53 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>                                     SCROLL ==> CSR
CURR WIN ==> 1          ALT WIN ==>
W1 =EVTS=====CMQM=====01JUL2002==16:03:46===MVMQS===D===45
CMD Event
--- Source
    Java VM
    McLogEvent
    McUpdate
    MsiInstaller
    MQSeries
    MQSiv2NeonPlugins
    MQSiv201
    MQSiv202
    Ntbackup.ini
    PatrolAgent
    Perfctrs
    Perflib
    Perfmon
    PerlMsg
    Profile Maker
    Replicator
    ReInitAgent
    SMS Client
```

Step 2 In the CMD column of the application for which you want to view events, type **S** and press **Enter**.

The WMQI Event Browse View is displayed.

Step 3 Overtyping one or both of the following fields as necessary, then press **Enter**:

- **Starting Location**, type the position of the first event you would like to display
- **Number to Retrieve**, type the number of events you would like to display

The WMQI Event view (Figure 3-6) displays a list of events.

Figure 3-6 WMQI Events List

```
01JUL2002 16:05:08 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>
CURR WIN ==> 1          ALT WIN ==>
>W1 =EVTSQ=====CMQM=====01JUL2002==16:05:06===MVMQS===D===66
CMD   Event Event      Event      Event      Event      Event
---   Number Severity   Date       Time       Ident      Source
2261  ERROR           07/01/2002 05:58:05PM  9999      MQSeries
2260  ERROR           07/01/2002 05:58:04PM  9202      MQSeries
2259  INFO            07/01/2002 05:58:03PM  9002      MQSeries
2258  ERROR           07/01/2002 05:37:58PM  9999      MQSeries
2257  ERROR           07/01/2002 05:37:57PM  9202      MQSeries
2256  INFO            07/01/2002 05:37:56PM  9002      MQSeries
2253  ERROR           07/01/2002 05:17:57PM  9999      MQSeries
2252  ERROR           07/01/2002 05:17:57PM  9202      MQSeries
2251  INFO            07/01/2002 05:17:55PM  9002      MQSeries
2250  ERROR           07/01/2002 04:57:54PM  9999      MQSeries
2249  ERROR           07/01/2002 04:57:54PM  9202      MQSeries
2248  INFO            07/01/2002 04:57:52PM  9002      MQSeries
2247  ERROR           07/01/2002 04:37:53PM  9999      MQSeries
2246  ERROR           07/01/2002 04:37:52PM  9202      MQSeries
2245  INFO            07/01/2002 04:37:51PM  9002      MQSeries
2242  ERROR           07/01/2002 04:17:51PM  9999      MQSeries
2241  ERROR           07/01/2002 04:17:50PM  9202      MQSeries
2240  INFO            07/01/2002 04:17:49PM  9002      MQSeries
```

Step 4 To view details for a particular event, type **S** in the CMD column for that event and press **Enter**.

The WMQI Event Details view (Figure 3-7) is displayed.

Figure 3-7 WMQI Event Details

```

01JUL2002 16:05:58 ----- MAINVIEW WINDOW INTERFACE(V4.1.01)-----
COMMAND ==>                                SCROLL ==> CSR
CURR WIN ==> 1          ALT WIN ==>
W1 =EVTSQD=====CMQM=====*=====01JUL2002==16:05:57====MVMQS====D====1
Event Source          MQSeries
Event Number          2258
Event Identity        9999
Event Severity        ERROR
Event Date            07/01/2002
Event Time            05:37:58PM
Event Description     Channel program ended abnormally.      Channel p
                      rogram 'CMQM.TO.CSQ1' ended abnormally.      Loo
                      k at previous error messages for channel program '
                      CMQM.TO.CSQ1' in the error files to determine the
                      cause of the failure.

```

Exiting from MAINVIEW for WebSphere MQ Integrator

When you are finished working with MAINVIEW for WebSphere MQ Integrator, you can return to the MAINVIEW Selection Menu in one of two ways:

1. Press the PF3 key, or
2. Issue one of the following commands from the command list:
 - Quit
 - RETURN

Chapter 4 Setting Alarms

MAINVIEW[®] Alarm Manager works with MAINVIEW for WebSphere MQ Integrator, and other MAINVIEW products, to provide alarms. These alarms display messages that can alert you when system resources are overused.

This chapter contains the following sections:

MAINVIEW Alarm Manager	4-2
MAINVIEW for WebSphere MQ Integrator Alarms	4-2

MAINVIEW Alarm Manager

MAINVIEW Alarm Manager is a tool that, with other MAINVIEW products, notifies you when an exception condition occurs. MAINVIEW Alarm Manager can monitor multiple systems simultaneously. You can display a single view that shows exceptions for all MAINVIEW performance monitors within your MVS enterprise.

Any data element on any MAINVIEW product can be used to generate alarms that produce the following results:

- create MVS console or subsystem messages
- display messages in a MAINVIEW Alarm Manager view that let you hyperlink to the MAINVIEW product which produced the exception
- trigger an automated alert or action from MAINVIEW® AutoOPERATOR™ for quick problem resolution

MAINVIEW Alarm Manager generates alarms when thresholds from specific MAINVIEW product views are exceeded. Alarms can be based on summarized data from multiple systems and subsystems that use MAINVIEW's single system image (SSI) capabilities.

Using MAINVIEW Alarm Manager, you can create and modify alarm definitions that display meaningful messages for your site's requirements. Alarms can be set for any (or all) severity levels, from informational to critical.

For more information about MAINVIEW Alarm Manager, see the *MAINVIEW Alarm Manager User Guide*.

MAINVIEW for WebSphere MQ Integrator Alarms

There are no sample alarms in this release of MAINVIEW for WebSphere MQ Integrator. However, you can set alarms to monitor the availability of the following components:

- message broker
- message flow
- configuration manager
- user name server

Glossary

HFS	Hierarchical File System. HFS extends IBM's traditional dataset architecture to a multi-level nested architecture like that used in Unix and other Distributed Systems. The HFS Component Directory stores target information that allows MAINVIEW for WebSphere MQ Integrator to access WMQI components.
PID	Process Identifier. Unique identifier assigned to a process by the operating system when the process starts. This identifier distinguishes the process as unique to the operating system and other programs.
UUID	Universal Unique Identifier. A 128-bit number used to uniquely identify an object or entity on the Internet.
USS	Unix System Services. A Unix system environment on z/OS that allows programs written for Unix or other Distributed Systems to be executed on IBM's z/OS. WebSphere MQ Integrator for z/OS uses Unix System Services to execute Distributed Systems broker code on z/OS.
WMQI	Abbreviation for IBM's WebSphere MQ Integrator message broker product.

Index

A

- accessing the product 3-2
- address spaces 1-3
- alarms 4-2
- application events, viewing 3-13
- architecture 1-3

B

- BBI-PAS address space 1-3
- brokers
 - monitoring 3-7
 - views 2-7

C

- changing properties 3-8
- components
 - displaying a list 3-5
 - displaying and changing properties 3-8
 - list view 2-6
 - monitoring 3-7
 - starting and stopping 3-10
- configuration manager views 2-13
- conventions
 - document xiv
 - syntax statements xv
 - typographical xiv

D

- displaying
 - components list 3-5
 - properties 3-8
- document conventions xiv
- documentation
 - electronic
 - online Help xiv
 - online xiv
 - related xii
- drilling down 2-5

E

- easy menus 2-2
 - EZISSI 2-4
 - EZMQI 2-2
- electronic documentation
 - online Help xiv
- events
 - selecting sources 3-13
 - viewing 3-13
 - views 2-16
- execution groups
 - monitoring 3-7
 - views 2-9
- exiting the product 3-16
- EZISSI easy menu 2-4
- EZMQI easy menu 2-2

F

features of product 1-2

H

HFS Component Directory 1-4

I

installation 1-4
interface, ISPF
 online Help xiv

L

license key 1-4

M

MAINVIEW Alarm Manager 4-2
MAINVIEW architecture 1-2
MAINVIEW for WebSphere MQ 1-4
message broker views 2-7
message flows
 monitoring 3-7
 views 2-10
monitoring
 broker components and resources 3-7
 Distributed Systems environments 1-5
mqbrkrs group 1-6
mqm group 1-6

N

Node Manager for MQ 1-3, 1-5
node views 2-12

O

online documentation xiv
online Help xiv
overview of the product 1-2

P

PAS user ID 1-6
platform requirements 1-4
product
 accessing 3-2
 architecture 1-3
 exiting 3-16
 installation 1-4
 overview 1-2
 views 2-5
properties, displaying and changing 3-8
PUT authority 1-6

Q

QM Profile 1-4

R

RACF 1-6
related documentation xii, xiv
release notes xiv
requirements
 for Distributed Systems 1-5
 for product 1-4
running traces 3-11

S

security 1-6
setting
 alarms 4-2
 targets 1-4
 trace attributes 3-11
Single System Image (SSI) mode 1-2
starting
 Node Manager for MQ 1-5
 traces 3-11
 WMQI components 3-10
stopping
 traces 3-11
 WMQI components 3-10
syntax statement conventions xv
SYSTEM.BROKER.* 1-6

T

targets 1-4

traces

- broker view 2-7

- execution group view 2-9

- message flow view 2-10

- starting and stopping 3-11

- user name server view 2-14

typographical conventions xiv

U

user name server

- monitoring 3-7

- views 2-14

V

viewing application events 3-13

views 2-5

- BKRZOS 2-7

- BKRZOSD 2-7

- BROKER 2-7

- BROKERD 2-7

- CFGMGR 2-13

- CFGMGRD 2-13

- EGQS 2-12

- EGQZ 2-12

- EGTRACE 2-9

- EVTS 2-16

- EVTSQ 2-16

- EVTSQD 2-16

- EVTZQ 2-16

- EXECGRP 2-9

- EXECGRPD 2-9

- MBQS 2-12

- MBQZ 2-12

- MBTRACE 2-7

- MFQS 2-12

- MFQZ 2-12

- MFTRACE 2-10

- MSGFLOW 2-10

- MSGFLOWD 2-10

- NODE 2-12

- NODED 2-12

NODEZ 2-12

UNSVR 2-14

UNSVRD 2-14

UNSZOS 2-14

UNSZOSD 2-14

UNTRACE 2-14

WMQI Components List 2-6

W

Windows events, viewing 3-13

STOP!

IMPORTANT INFORMATION - DO NOT INSTALL THIS PRODUCT UNLESS YOU HAVE READ ALL OF THE FOLLOWING MATERIAL

By clicking the YES or ACCEPT button below (when applicable), or by installing and using this Product or by having it installed and used on your behalf, You are taking affirmative action to signify that You are entering into a legal agreement and are agreeing to be bound by its terms, EVEN WITHOUT YOUR SIGNATURE. BMC is willing to license this Product to You ONLY if You are willing to accept all of these terms. CAREFULLY READ THIS AGREEMENT. If You DO NOT AGREE with its terms, DO NOT install or use this Product; press the NO or REJECT button below (when applicable) or promptly contact BMC or your BMC reseller and your money will be refunded if by such time You have already purchased a full-use License.

SOFTWARE LICENSE AGREEMENT FOR BMC PRODUCTS

SCOPE. This is a legally binding Software License Agreement (“License”) between You (either an individual or an entity) and BMC pertaining to the original computer files (including all computer programs and data stored in such files) contained in the enclosed Media (as defined below) or made accessible to You for electronic delivery, if as a prerequisite to such accessibility You are required to indicate your acceptance of the terms of this License, and all whole or partial copies thereof, including modified copies and portions merged into other programs (collectively, the “Software”). “Documentation” means the related hard-copy or electronically reproducible technical documents furnished in association with the Software, “Media” means the original BMC-supplied physical materials (if any) containing the Software and/or Documentation, “Product” means collectively the Media, Software, and Documentation, and all Product updates subsequently provided to You, and “You” means the owner or lessee of the hardware on which the Software is installed and/or used. “BMC” means BMC Software Distribution, Inc. unless You are located in one of the following regions, in which case “BMC” refers to the following indicated BMC Software, Inc. subsidiary: (i) Europe, Middle East or Africa --BMC Software Distribution, B.V., (ii) Asia/Pacific -- BMC Software Asia Pacific Pte Ltd., (iii) Brazil -- BMC Software do Brazil, or (iv) Japan -- BMC Software K.K. If You enter into a separate, written software license agreement signed by both You and BMC or your authorized BMC reseller granting to you the rights to install and use this Product, then the terms of that separate, signed agreement will apply and this License is void.

FULL-USE LICENSE. Subject to these terms and payment of the applicable license fees, BMC grants You this non-exclusive License to install and use one copy of the Software for your internal use on the number(s) and type(s) of servers or workstations for which You have paid or agreed to pay to BMC or your BMC reseller the appropriate license fee. If your license fee entitles You only to a License having a limited term, then the duration of this License is limited to that term; otherwise this License is perpetual, subject to the termination provisions below.

TRIAL LICENSE. If You have not paid or agreed to pay to BMC or your BMC Reseller the appropriate license fees for a full use license, then, **NOTWITHSTANDING ANYTHING TO THE CONTRARY CONTAINED IN THIS LICENSE:** (i) this License consists of a non-exclusive evaluation license (“Trial License”) to use the Product for a limited time (“Trial Period”) only for evaluation; (ii) during the Trial Period, You may not use the Software for development, commercial, production, database management or other purposes than those expressly permitted in clause (i) immediately above; and (iii) your use of the Product is on an **AS IS** basis, and **BMC, ITS RESELLERS AND LICENSORS GRANT NO WARRANTIES OR CONDITIONS (INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE) TO YOU AND ACCEPT NO LIABILITY WHATSOEVER RESULTING FROM THE USE OF THIS PRODUCT UNDER THIS TRIAL LICENSE.** If You use this Product for other than evaluation purposes or wish to continue using it after the Trial Period, you must purchase a full-use license. When the Trial Period ends, your right to use this Product automatically expires, though in certain cases You may be able to extend the term of the Trial Period by request. Contact BMC or your BMC reseller for details.

TERM AND TERMINATION. This License takes effect on the first to occur of the date of shipment or accessibility to You for electronic delivery, as applicable (the “Product Effective Date”). You may terminate this License at any time for any reason by written notice to BMC or your BMC reseller. This License and your right to use the Product will terminate automatically with or without notice by BMC if You fail to comply with any material term of this License. Upon termination, You must erase or destroy all components of the Product including all copies of the Software, and stop using or accessing the Software. Provisions concerning Title and Copyright, Restrictions (or Restricted Rights, if You are a U.S. Government entity) or limiting BMC’s liability or responsibility shall survive any such termination.

TITLE AND COPYRIGHT; RESTRICTIONS. All title and copyrights in and to the Product, including but not limited to all modifications thereto, are owned by BMC and/or its affiliates and licensors, and are protected by both United States copyright law and applicable international copyright treaties. You will not claim or assert title to or ownership of the Product. To the extent expressly permitted by applicable law or treaty notwithstanding this limitation, You may copy the Software only for backup or archival purposes, or as an essential step in utilizing the Software, but for no other purpose. You will not remove or alter any copyright or proprietary notice from copies of the Product. You acknowledge that the Product contains valuable trade secrets of BMC and/or its affiliates and licensors. Except in accordance with the terms of this License, You agree (a) not to decompile, disassemble, reverse engineer or otherwise attempt to derive the Software’s source code from object code except to the extent expressly permitted by applicable law or treaty despite this limitation; (b) not to sell, rent, lease, license, sublicense, display, modify, time share, outsource or otherwise transfer the Product to, or permit the use of this Product by, any third party; and (c) to use reasonable care and protection to prevent the unauthorized use, copying, publication or dissemination of the Product and BMC confidential information learned from your use of the Product. **You will not export or re-export any Product without both the written consent of BMC and the appropriate U.S. and/ or foreign government license(s) or license exception(s).** Any programs, utilities, modules or other software or documentation created, developed, modified or enhanced by or for You using this Product shall likewise be subject to these restrictions. BMC has the right to obtain injunctive relief against any actual or threatened violation of these restrictions, in addition to any other available remedies. Additional restrictions may apply to certain files, programs or data supplied by third parties and embedded in the Product; consult the Product installation instructions or Release Notes for details.

LIMITED WARRANTY AND CONDITION. If You have purchased a Full-Use License, BMC warrants that (i) the Media will be, under normal use, free from physical defects, and (ii) for a period of ninety (90) days from the Product Effective Date, the Product will perform in substantial accordance with the operating specifications contained in the Documentation that is most current at the Product Effective Date. BMC’s entire liability and your exclusive remedy under this provision will be for BMC to use reasonable best efforts to remedy defects covered by this warranty

and condition within a reasonable period of time or, at BMC's option, either to replace the defective Product or to refund the amount paid by You to license the use of the Product. BMC and its suppliers do not warrant that the Product will satisfy your requirements, that the operation of the Product will be uninterrupted or error free, or that all software defects can be corrected. This warranty and condition shall not apply if: (i) the Product is not used in accordance with BMC's instructions, (ii) a Product defect has been caused by any of your or a third party's malfunctioning equipment, (iii) any other cause within your control causes the Product to malfunction, or (iv) You have made modifications to the Product not expressly authorized in writing by BMC. No employee, agent or representative of BMC has authority to bind BMC to any oral representations, warranties or conditions concerning the Product. **THIS WARRANTY AND CONDITION IS IN LIEU OF ALL OTHER WARRANTIES AND CONDITIONS. THERE ARE NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THIS LICENSE OR ANY PRODUCT LICENSED HEREUNDER. THIS PARAGRAPH SHALL NOT APPLY TO A TRIAL LICENSE.** Additional support and maintenance may be available for an additional charge; contact BMC or your BMC reseller for details.


LIMITATION OF LIABILITY. Except as stated in the next succeeding paragraph, BMC's and your BMC reseller's total liability for all damages in connection with this License is limited to the price paid for the License. **IN NO EVENT SHALL BMC BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, PUNITIVE OR INDIRECT DAMAGES OF ANY KIND ARISING OUT OF THE USE OF THIS PRODUCT (SUCH AS LOSS OF PROFITS, GOODWILL, BUSINESS, DATA OR COMPUTER TIME, OR THE COSTS OF RECREATING LOST DATA), EVEN IF BMC HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.** Some jurisdictions do not permit the limitation of consequential damages so the above limitation may not apply.

INDEMNIFICATION FOR INFRINGEMENT. BMC will defend or settle, at its own expense, any claim against You by a third party asserting that your use of the Product within the scope of this License violates such third party's patent, copyright, trademark, trade secret or other proprietary rights, and will indemnify You against any damages finally awarded against You arising out of such claim. However, You must promptly notify BMC in writing after first receiving notice of any such claim, and BMC will have sole control of the defense of any action and all negotiations for its settlement or compromise, with your reasonable assistance. BMC will not be liable for any costs or expenditures incurred by You without BMC's prior written consent. If an order is obtained against your use of the Product by reason of any claimed infringement, or if in BMC's opinion the Product is likely to become the subject of such a claim, BMC will at its option and expense either (i) procure for You the right to continue using the product, or (ii) modify or replace the Product with a compatible, functionally equivalent, non-infringing Product, or (iii) if neither (i) nor (ii) is practicable, issue to You a pro-rata refund of your paid license fee(s) proportionate to the number of months remaining in the 36 month period following the Product Effective Date. This paragraph sets forth your only remedies and the total liability to You of BMC, its resellers and licensors arising out of such claims.

GENERAL. This License is the entire understanding between You and BMC concerning this License and may be modified only in a mutually signed writing between You and BMC. If any part of it is invalid or unenforceable, that part will be construed, limited, modified, or, severed so as to eliminate its invalidity or unenforceability. This License will be governed by and interpreted under the laws of the jurisdiction named below, without regard to conflicts of law principles, depending on which BMC Software, Inc. subsidiary is the party to this License: (i) BMC Software Distribution, Inc. - the State of Texas, U.S.A., (ii) BMC Software Distribution, B.V. - The Netherlands, (iii) BMC Software Asia Pacific Pte Ltd. -- Singapore (iv) BMC Software do Brazil -- Brazil, or (v) BMC Software K.K. -- Japan. Any person who accepts or signs changes to the terms of this License promises that they have read and understood these terms, that they have the authority to accept on your behalf and legally obligate You to this License. Under local law and treaties, the restrictions and limitations of this License may not apply to You; You may have other rights and remedies, and be subject to other restrictions and limitations.

U.S. GOVERNMENT RESTRICTED RIGHTS. UNPUBLISHED -- RIGHTS RESERVED UNDER THE COPYRIGHT LAWS OF THE UNITED STATES. Use, duplication, or disclosure by the U.S. Government is subject to restrictions set forth in FAR Section 52.227-14 Alt. III (g)(3), FAR Section 52.227-19, DFARS 252.227-7014 (b) or DFARS 227.7202, as amended from time to time. Contractor/Manufacturer is BMC Software, Inc., 2101 CityWest Blvd., Houston, TX 77042-2827, USA. Any contract notices should be sent to this address.

Notes



17861